

ATP DDR1 DRAM Solutions

Intense Performance for Intense Workloads



Double Data Rate (DDR), also known as DDR1, is the second generation of Synchronous DRAM (SDRAM). As its name implies, double data rate refers to its ability to read and write data on both the rising and falling of the system clock to achieve nearly twice the bandwidth of single data rate (SDR) SDRAM.

JEDEC developed the DDR SDRAM specification (JESD79) in 2000 and was an advancement over SDRAM technology with increased memory bandwidth and performance. ATP DDR1 modules have 400 MT/s transfer speeds and run at 2.5V, significantly cutting power consumption compared with SDRAM's 3.3V.

Key Features

- Chipkill support
- Legacy system support

Applications

- Networking systems
- Telecommunication
- Gaming
- Healthcare
- Industrial PCs









Specifications

DDR						
DIMM Type	ECC UDIMM	Non-ECC UDIMM	ECC SO-DIMM	Non-ECC SO-DIMM		
Density	512 MB	256 MB	256 MB to 512 MB / 1 GB	128 MB to 512 MB / 1 GB		
Speed up to (MT/s)	400	400	400	400		
PCB Height	Low Profile	Low Profile	Low Profile	Low Profile		
Operating Temperature	0°C to 85°C	0°C to 85°C	0°C to 85°C	0°C to 85°C / -40°C to 95°C		

DDR					
Module Type	SO-DIMM	SO-DIMM (Industrial Grade)	UDIMM	SO-DIMM	
Function	Unbuffered Non-ECC	Unbuffered Non-ECC	Unbuffered ECC / Unbuffered Non ECC	Unbuffered ECC	
Density	128 MB / 256 MB / 512 MB / 1 GB	256 MB / 512 MB	256 MB / 512 MB	256 MB / 512 MB / 1 GB	
Frequency	400 MHz	400 MHz	400 MHz	400 MHz	
PCB Height	1.25"	1.25"	1.25"	1.25"	
Number of Pins	200	200	184	200	
Solutions	Standard	Standard	Build To Order (BTO)	Build To Order (BTO)	



To learn more about this product, contact your ATP Representative.

ATP Global Footprint

ATP TAIWAN(HQ)
TEL: +886-2-2659-6368
FAX: +886-2-2659-4982
sales-apac@atpinc.com

ATP USA

TEL: +1-408-732-5000 FAX: +1-408-732-5055 sales@atpinc.com ATP EUROPE

TEL: +49-89-374-9999-0 FAX: +49-89-374-9999-29 sales-europe@atpinc.com ATP JAPAN

TEL: +81-3-6260-0797 FAX: +81-3-6260-0798 sales-japan@atpinc.com ATP CHINA

TEL: +86-21-5080-2220 FAX: +86-21-9687-0000-026 sales@cn.atpinc.com